Amendment to the Claims:

This listing of claims 1-12 will replace all prior versions, and listing of claims in the

application.

**Listing of Claims** 

1. (Currently Amended) A high-pressure discharge lamp comprising: a discharge vessel

(10) enclosing a discharge space (11) which contains an ionizable filling, the discharge

vessel (10) having a first (2) and a second (3) mutually opposed neck-shaped portion

provided with a pair of electrodes (6, 7) arranged in the discharge space (13), each

electrode (6, 7) being tubular over its entire length, at least one of the electrodes (6, 7)

being directly coupled at an end not arranged in the discharge space, to a rod (15) which

is coupled at a distal end to a current-supply conductor (5), a melting-ceramic joint (21)

being provided between the current-supply conductor (5), the rod (15) and a wall of the

respective first (2) and a second (3) mutually opposed neck-shaped portions, thereby

providing a gas-tight closure of the discharge space.

2. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein

characterized in that the electrodes (6, 7) are free from coils in the discharge space (13).

3. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein

characterized in that the electrodes (6, 7) extend to outside the discharge vessel (10).

5

- 4. (Currently Amended) A high-pressure discharge lamp as claimed in claim 3, wherein characterized in that the electrodes (6, 7) are each partially filled with a rod (1115) welded to a side of the electrodes (6, 7) facing away from the discharge space (13).
- 5. (Currently Amended) A high-pressure discharge lamp as claimed in claim 4, characterized in that the rod (1+15) extends into the discharge space (13).
- 6. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein eharacterized in that-the ratio between the inner diameter d<sub>in</sub> and the outer diameter d<sub>out</sub> of the electrodes (6, 7) is in the range:

$$0.2 < d_{in} / d_{out} < 0.8$$
.

- 7. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein characterized in that the inner diameter of the tubular electrodes (6, 7) is at least 20 µm.
- 8. (Currently Amended) A high-pressure discharge lamp as claimed in claim 2, wherein characterized in that the ratio of the outer diameter d<sub>out</sub> of the tubular electrodes (6, 7) and the inner diameter d<sub>nsp</sub> of the neck-shaped portions (2, 3) is in the range:

$$0.2~\leq~d_{out}~/~d_{nsp}~\leq~0.8.$$

9. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein characterized in that the electrodes (6, 7) are made of tungsten.

10. (Currently Amended) A high-pressure discharge lamp as claimed in claim 1, wherein characterized in that the ratio between the electric current  $I_{mhl}$  of the high-pressure discharge lamp and the outer diameter  $d_{out}$  of the electrodes (6, 7) is in the range:

$$2 \le I_{mhl} / (d^2_{out} / d^2_{in}) \le 6,$$

wherein the electric current is expressed in amperes and the diameter in millimeters.

- 11. (New) A high-pressure discharge lamp as claimed in claim 1, wherein the rod (15) is made from one of molybdenum or cermet.
- 12. (New) A high-pressure discharge lamp as claimed in claim 1, wherein the current-supply conductor (5) is made from niobium.